

JAC
MOTORS



JAC N56 3 TON CHASSIS CAB TRUCK

SPECIFICATIONS

JACMOTORS.CO.ZA

Contact Your Nearest Group1 JAC Dealership

JAC Alberton
Gauteng
010 593 4393

JAC Strand
Western Cape
021 891 2866

We Deliver Nationwide
www.group1jac.co.za

N56 3 Ton Truck

DESCRIPTION		N56 3 TON CHASSIS CAB
Mass Data (kg)	GVM	5 600
	GCM	6 350
	Tare Mass	2 100
	Tare Front	1 364
	Tare Rear	736
	GAWR Front	2 000
	GAWR Rear	4 000
Approximate Body & Payload		3 350
Dimensional Data (mm)	Overall Length - OAL	5 960
	Wheelbase - WB	3 360
	Overall Width - OW	1 860
	Cab Width (Excluding Mirrors) - CW	1 725
	Overall Height - OH	2 215
	Bumper To Back Of Cab - BBC	1 565
	Cab to Axle - CA	2 820
	Cab To End Of Frame - CE	4 310
	Front Overhang - FOH	1 110
	Rear Overhang - ROH	1 490
	Ground Clearance (Rear Axle)	220
	Frame Width	700
	Rear Track - RT	1 425
Engine	Make	JAC
	Model	HFCC4DA1-2B1
	Configuration	Inline 4 Cylinder
	Capacity (cc)	2 771
	Emission Level	Euro II
	Type	4 Stroke Diesel Turbocharged Intercooled
	Injector Type	Common Rail Pump
	Engine Oil Cooler	Yes
	Valve Configuration	OHV
	Power @ RPM (kW)	68 kW @ 3 600
	Torque @ RPM (Nm)	216 Nm @ 1 800 - 2 200
Transmission	Make	JAC
	Model	LC5T255N3
	Type	Synchromesh (2 - 5 Only)
	Shift	Manual
	No. Of Forward Gears	5
	First Gear Ratio	5.529 : 1
	Reverse Gear Ratio	5.271 : 1
Safety	Reverse Alarm	Yes
	Seat Belt Warning	Yes
	Height Adjustable Seat Belt	Driver
	Height Adjustable Headlights	Yes
	Daytime Running Lights	Yes
	Antilock Braking System (ABS)	Yes
	Microdot Vehicle Identification	Yes

DESCRIPTION		N56 3 TON CHASSIS CAB
Clutch	Type	Diaphragm Spring
	Diameter (mm)	250
	Operation	Vacuum Assistance
Suspension	Front & Rear	Multi-Leaf Spring With Shock Absorbers
	Steering	Steering Column
Steering	Type	Recirculating Ball
	Operation	Power Assisted
Brakes	Type	Hydraulic Assisted
	Anti-Lock Braking System (ABS)	Yes
	Front	Disc
	Rear	Drum
	Parking Brake	Rear Of Transmission
	Exhaust Brake	Yes
Fuel Tank	Material	Plastic
	Capacity (Litres)	100
	Lockable Fuel Cap	Yes
Vehicle Performance	Maximum Gradeability (%)	24
	Max Geared Speed (km/h)	100
	Maximum Allowable Speed (km/h) (SA SL)	100
Electrical Equipment	System	12V
	Battery System	2 X 80A-H
	Alternator	12V 60 Amp
	Starter	12V 2.8kW
Wheels & Tyres	Wheel Type	Single Piece Steel
	Wheel Attachment	5 Stud
	No. Of Wheels Including Spare	7
	Spare Wheel Carrier Location	Rear Of Frame
	Tyre Size	205/75R17.5 14PLY
Comfort Configuration	Air Conditioning	Yes
	Heater	Yes
	Power Windows	Yes
	Central Locking	Yes
	Number Of Seats	3
	12V Accessory Power Outlet	Yes
	Radio	AM/FM With AUX And USB
Cup Holders	Yes	



JAC WARRANTY & SERVICE PLAN

- 5 Year / 150 000km Warranty
- 5 Year / 60 000km Service Plan

Service intervals:

- 5 000km / 6 Months
- 15 000km / 12 Months
- 25 000km / 24 Months

* Thereafter every 10 000km / 12 Months



BETTER DRIVE | BETTER LIFE

*Terms & Conditions apply. Offer available while stocks last. Prices may change without any prior notification. Images used are for illustrative purposes only. Actual products and specifications may vary from above information.

JAC
MOTORS



JAC N56 3 TON DROPSIDE TRUCK

SPECIFICATIONS

JACMOTORS.CO.ZA

N56 3 Ton Truck

DESCRIPTION		N56 3 TON DROPSIDE
Mass Data (kg)	GVM	5 600
	GCM	6 350
	Tare Mass	2 560
	Tare Front	1 460
	Tare Rear	1 100
	GAWR Front	2 000
	GAWR Rear	4 000
	Approximate Body & Payload	3 040
Dimensional Data (mm)	Overall Length - OAL	5 995
	Wheelbase - WB	3 360
	Overall Width - OW	1 900
	Cab Width (Excluding Mirrors) - CW	1 725
	Overall Height - OH	2 330
	Bumper To Back Of Cab - BBC	1 565
	Cab to Axle - CA	2 820
	Cab To End Of Frame - CE	4 310
	Front Overhang - FOH	1 110
	Rear Overhang - ROH	1 525
	Ground Clearance (Rear Axle)	220
	Frame Width	700
	Rear Track - RT	1 425
	Dropside Body Inner Length	4 230
	Dropside Body Inner Width	1 810
Dropside Side Height	400	
Engine	Make	JAC
	Model	HFCC4DA1-2B1
	Configuration	Inline 4 Cylinder
	Capacity (cc)	2 771
	Emission Level	Euro II
	Type	4 Stroke Diesel Turbocharged Intercooled
	Injector Type	Common Rail Pump
	Engine Oil Cooler	Yes
	Valve Configuration	OHV
	Power @ RPM (kW)	68 kW @ 3 600
Torque @ RPM (Nm)	216 Nm @ 1 800 - 2 200	
Transmission	Make	JAC
	Model	LC5T255N3
	Type	Synchromesh (2 - 5 Only)
	Shift	Manual
	No. Of Forward Gears	5
	First Gear Ratio	5.529 : 1
	Reverse Gear Ratio	5.271 : 1
Safety	Reverse Alarm	Yes
	Seat Belt Warning	Yes
	Height Adjustable Seat Belt	Driver
	Height Adjustable Headlights	Yes
	Daytime Running Lights	Yes
	Antilock Braking System (ABS)	Yes
	Microdot Vehicle Identification	Yes

DESCRIPTION		N56 3 TON DROPSIDE
Clutch	Type	Diaphragm Spring
	Diameter (mm)	250
	Operation	Vacuum Assistance
Suspension	Front & Rear	Multi-Leaf Spring With Shock Absorbers
Steering	Steering Column	Tilt And Telescoping
	Type	Recirculating Ball
	Operation	Power Assisted
Brakes	Type	Hydraulic Assisted
	Anti-Lock Braking System (ABS)	Yes
	Front	Disc
	Rear	Drum
	Parking Brake	Rear Of Transmission
	Exhaust Brake	Yes
Fuel Tank	Material	Plastic
	Capacity (Litres)	100
	Lockable Fuel Cap	Yes
Vehicle Performance	Maximum Gradeability (%)	24
	Max Geared Speed (km/h)	100
	Maximum Allowable Speed (km/h) (SA SL)	100
Electrical Equipment	System	12V
	Battery System	2 X 80A-H
	Alternator	12V 60 Amp
	Starter	12V 2.8kW
Wheels & Tyres	Wheel Type	Single Piece Steel
	Wheel Attachment	5 Stud
	No. Of Wheels Including Spare	7
	Spare Wheel Carrier Location	Rear Of Frame
	Tyre Size	205/75R17.5 14PLY
Comfort Configuration	Air Conditioning	Yes
	Heater	Yes
	Power Windows	Yes
	Central Locking	Yes
	Number Of Seats	3
	12V Accessory Power Outlet	Yes
	Radio	AM/FM With AUX And USB
	Cup Holders	Yes
	Lockable Toolbox At Rear Of Frame	Yes



JAC WARRANTY & SERVICE PLAN

- 5 Year / 150 000km Warranty
- 5 Year / 60 000km Service Plan

Service intervals:

- 5 000km / 6 Months
- 15 000km / 12 Months
- 25 000km / 24 Months

* Thereafter every 10 000km / 12 Months



BETTER DRIVE | BETTER LIFE

*Terms & Conditions apply. Offer available while stocks last. Prices may change without any prior notification. Images used are for illustrative purposes only. Actual products and specifications may vary from above information.

JAC
MOTORS



JAC N90 6 TON CHASSIS CAB TRUCK

SPECIFICATIONS

JACMOTORS.CO.ZA

N90 6 Ton Truck

	DESCRIPTION	N90 6 TON CHASSIS CAB
Mass Data (kg)	GVM	9 000
	GCM	12 500
	Tare Mass	3 000
	Tare Front	1 850
	Tare Rear	1 150
	GAWR Front	3 100
	GAWR Rear	6 600
	Approximate Body & Payload	5 920
Dimensional Data (mm)	Overall Length - OAL	6 970
	Wheelbase - WB	3 845
	Overall Width - OW	2 110
	Cab Width (Excluding Mirrors) - CW	1 995
	Overall Height - OH	2 300
	Bumper To Back Of Cab - BBC	1 680
	Cab to Axle - CA	3 245
	Cab To End Of Frame - CE	5 255
	Front Overhang - FOH	1 110
	Rear Overhang - ROH	2 010
	Ground Clearance (Rear Axle)	210
	Frame Width	850
	Rear Track - RT	1 650
	Engine	Make
Model		ISF 3.8
Configuration		Inline 4 Cylinder
Capacity (cc)		3 800
Emission Level		Euro III
Type		4 Stroke Diesel Turbocharged Intercooled
Injector Type		Common Rail Pump
Engine Oil Cooler		Yes
Valve Configuration		OHV
Power @ RPM (kW)		115 @ 2600
Torque @ RPM (Nm)	500 @ 1200 - 1900	
Transmission	Make	JAC
	Model	LC6T540B
	Type	Synchromesh (2 - 6 Only)
	Shift	Manual
	No. Of Forward Gears	6
	First Gear Ratio	6.091 : 1
	Reverse Gear Ratio	5.645 : 1
Safety	Reverse Alarm	Yes
	Seat Belt Warning	Yes
	Height Adjustable Seat Belt	Driver
	Height Adjustable Headlights	Yes
	LED Daytime Running Lights	Yes
	Antilock Braking System (ABS)	Yes
	Microdot Vehicle Identification	Yes

	DESCRIPTION	N90 6 TON CHASSIS CAB
Clutch	Type	Diaphragm Spring
	Diameter (mm)	350
	Operation	Hydraulic Assistance
Suspension	Front & Rear	Multi-Leaf Spring With Shock Absorbers
	Steering Column	Tilt And Telescoping
Steering	Type	Recirculating Ball
	Operation	Power Assisted
Brakes	Type	Dual Circuit Air Brakes
	Anti-Lock Braking System (ABS)	Yes
	Air Dryer	Yes
	Front	Drum
	Rear	Drum
	LSP Valve On Rear Axle	Yes
	Parking Brake	Spring Brake On Rear Wheels
	Exhaust Brake	Yes
Fuel Tank	Material	Steel
	Capacity (Litres)	114
	Lockable Fuel Cap	Yes
Vehicle Performance	Maximum Gradeability (%)	30
	Max Geared Speed (km/h)	105
	Maximum Allowable Speed (km/h) (SA SL)	80
Electrical Equipment	System	24V
	Battery System	2 X 80A-H
	Alternator	24V 70 Amp
	Starter	24V 3.6kW
Wheels & Tyres	Wheel Type	Single Piece Steel
	Wheel Attachment	6 Stud
	No. Of Wheels Including Spare	7
	Spare Wheel Carrier Location	Rear Of Frame
Comfort Configuration	Tyre Size	215/75R17.5 16PLY
	Air Conditioning	Yes
	Heater	Yes
	Power Windows	Yes
	Central Locking	Yes
	Number Of Seats	3
	12V Accessory Power Outlet	Yes
Radio	AM/FM With AUX And USB	
Cup Holders	Yes	
Lockable Toolbox At Rear Of Frame	Yes	



JAC WARRANTY & SERVICE PLAN

- 2 Year / Unlimited km Warranty
- Service Plan Available On Request

Service intervals:

- 10 000km / 3 Months
- 25 000km / 6 Months
- 40 000km / 12 Months

* Thereafter every 15 000km / 6 Months



BETTER DRIVE | BETTER LIFE

*Terms & Conditions apply. Offer available while stocks last. Prices may change without any prior notification. Images used are for illustrative purposes only. Actual products and specifications may vary from above information.

JAC
MOTORS



JAC N90 6 TON DROPSIDE TRUCK

SPECIFICATIONS

JACMOTORS.CO.ZA

N90 6 Ton Truck

DESCRIPTION		N90 6 TON DROPSIDE
Mass Data (kg)	GVM	9 000
	GCM	12 500
	Tare Mass	3 800
	Tare Front	1 965
	Tare Rear	1 835
	GAWR Front	3 100
	GAWR Rear	6 600
	Approximate Body & Payload	5 200
Dimensional Data (mm)	Overall Length - OAL	7 030
	Wheelbase - WB	3 845
	Overall Width - OW	2 275
	Cab Width (Excluding Mirrors) - CW	1 995
	Overall Height - OH	2 300
	Bumper To Back Of Cab - BBC	1 680
	Cab to Axle - CA	3 245
	Cab To End Of Frame - CE	5 255
	Front Overhang - FOH	1 110
	Rear Overhang - ROH	2 078
	Ground Clearance (Rear Axle)	210
	Frame Width	850
	Rear Track - RT	1 650
	Dropside Body Inner Length	5 135
	Dropside Inner Width	2 110
Dropside Side Height	550	
Engine	Make	Cummins
	Model	ISF 3.8
	Configuration	Inline 4 Cylinder
	Capacity (cc)	3 800
	Emission Level	Euro III
	Type	4 Stroke Diesel Turbocharged Intercooled
	Injector Type	Common Rail Pump
	Engine Oil Cooler	Yes
	Valve Configuration	OHV
	Power @ RPM (kW)	115 @ 2600
Torque @ RPM (Nm)	500 @ 1200 - 1900	
Transmission	Make	JAC
	Model	LC6T540B
	Type	Synchromesh (2 - 6 Only)
	Shift	Manual
	No. Of Forward Gears	6
	First Gear Ratio	6.091 : 1
	Reverse Gear Ratio	5.645 : 1
Safety	Reverse Alarm	Yes
	Seat Belt Warning	Yes
	Height Adjustable Seat Belt	Driver
	Height Adjustable Headlights	Yes
	LED Daytime Running Lights	Yes
	Antilock Braking System (ABS)	Yes
	Microdot Vehicle Identification	Yes

DESCRIPTION		N90 6 TON DROPSIDE
Clutch	Type	Diaphragm Spring
	Diameter (mm)	350
	Operation	Hydraulic Assistance
Suspension	Front & Rear	Multi-Leaf Spring With Shock Absorbers
	Steering Column	Tilt And Telescoping
Steering	Type	Recirculating Ball
	Operation	Power Assisted
	Brakes	Type
Anti-Lock Braking System (ABS)		Yes
Air Dryer		Yes
Front		Drum
Rear		Drum
LSP Valve On Rear Axle		Yes
Parking Brake		Spring Brake On Rear Wheels
Exhaust Brake		Yes
Fuel Tank	Material	Steel
	Capacity (Litres)	114
	Lockable Fuel Cap	Yes
Vehicle Performance	Maximum Gradeability (%)	30
	Max Geared Speed (km/h)	105
	Maximum Allowable Speed (km/h) (SA SL)	80
Electrical Equipment	System	24V
	Battery System	2 X 80A-H
	Alternator	24V 70 Amp
	Starter	24V 3.6kW
Wheels & Tyres	Wheel Type	Single Piece Steel
	Wheel Attachment	6 Stud
	No. Of Wheels Including Spare	7
	Spare Wheel Carrier Location	Rear Of Frame
	Tyre Size	215/75R17.5 16PLY
Comfort Configuration	Air Conditioning	Yes
	Heater	Yes
	Power Windows	Yes
	Central Locking	Yes
	Number Of Seats	3
	12V Accessory Power Outlet	Yes
	Radio	AM/FM With AUX And USB
	Cup Holders	Yes
Lockable Toolbox At Rear Of Frame	Yes	



JAC WARRANTY & SERVICE PLAN

- 2 Year / Unlimited km Warranty
- Service Plan Available On Request

Service intervals:

- 10 000km / 3 Months
- 25 000km / 6 Months
- 40 000km / 12 Months

* Thereafter every 15 000km / 6 Months



BETTER DRIVE | BETTER LIFE

*Terms & Conditions apply. Offer available while stocks last. Prices may change without any prior notification. Images used are for illustrative purposes only. Actual products and specifications may vary from above information.

JAC
MOTORS



JAC N140 9 TON CHASSIS CAB TRUCK

SPECIFICATIONS

JACMOTORS.CO.ZA

N140 9 Ton Truck

DESCRIPTION		N140 9 TON CHASSIS CAB
Mass Data (kg)	GVM	14 000
	GCM	16 000
	Tare Mass	3 950
	Tare Front	2 295
	Tare Rear	1 655
	GAWR Front	4 800
	GAWR Rear	9 200
Approximate Body & Payload		9 000
Dimensional Data (mm)	Overall Length - OAL	8 890
	Wheelbase - WB	5 300
	Overall Width - OW	2 348
	Cab Width (Excluding Mirrors) - CW	1 995
	Overall Height - OH	2 475
	Bumper To Back Of Cab - BBC	2 025
	Cab to Axle - CA	4 455
	Cab To End Of Frame - CE	6 865
	Front Overhang - FOH	1 180
	Rear Overhang - ROH	2 410
	Ground Clearance (Rear Axle)	230
	Frame Width	865
	Rear Track - RT	1 803
Engine	Make	Cummins
	Model	ISB 4.5
	Configuration	Inline 4 Cylinder
	Capacity (cc)	4 460
	Emission Level	Euro III
	Type	4 Stroke Diesel Turbocharged Intercooled
	Injector Type	Common Rail Pump
	Engine Oil Cooler	Yes
	Valve Configuration	OHV
	Power @ RPM (kW)	154 @ 2300
Torque @ RPM (Nm)	740 @ 1200 - 1800	
Transmission	Make	JAC
	Model	FAST C6J76T
	Type	Synchromesh (2 - 6 Only)
	Shift	Manual
	No. Of Forward Gears	6
	First Gear Ratio	6.09 : 1
	Reverse Gear Ratio	5.55 : 1
Safety	Reverse Alarm	Yes
	Seat Belt Warning	Yes
	Height Adjustable Seat Belt	Driver
	Steering Wheel Remote Controls	Cruise Control And Bluetooth Radio
	Height Adjustable Headlights	Yes
	LED Daytime Running Lights	Yes
	Antilock Braking System (ABS)	Yes
	Microdot Vehicle Identification	Yes

DESCRIPTION		N140 9 TON CHASSIS CAB
Clutch	Type	Diaphragm Spring
	Diameter (mm)	395
	Operation	Hydraulic Assistance
Suspension	Front & Rear	Multi-Leaf Spring With Shock Absorbers (Front)
Steering	Steering Column	Tilt And Telescoping
	Type	Recirculating Ball
	Operation	Power Assisted
Brakes	Type	Dual Circuit Air Brakes
	Anti-Lock Braking System (ABS)	Yes
	Air Dryer	Yes
	Front	Drum
	Rear	Drum
	LSP Valve On Rear Axle	Yes
	Parking Brake	Spring Brake On Rear Wheels
	Exhaust Brake	Yes
Fuel Tank	Material	Aluminium Alloy
	Capacity (Litres)	200
	Lockable Fuel Cap	Yes
Vehicle Performance	Maximum Gradeability (%)	30
	Max Geared Speed (km/h)	100
	Maximum Allowable Speed (km/h) (SA SL)	80
Electrical Equipment	System	24V
	Battery System	2 X 80A-H
	Alternator	24V 70 Amp
	Starter	24V 3.6kW
Wheels & Tyres	Wheel Type	Single Piece Steel
	Wheel Attachment	8 Stud
	No. Of Wheels Including Spare	7
	Spare Wheel Carrier Location	Rear Of Frame
	Tyre Size	255/70R22.5 16PLY
Comfort Configuration	Air Conditioning	Yes
	Heater	Yes
	Roof Air Vent	Yes
	Power Windows	Yes
	Central Locking	Yes
	Cruise Control	Yes
	Number Of Seats	3
	Number Of Bunks	1
	12V Accessory Power Outlet	Yes
	Radio	AM/FM Bluetooth With AUX And USB
	Cup Holders	Yes
Lockable Toolbox At Rear Of Frame	Yes	



JAC WARRANTY & SERVICE PLAN

- 2 Year / Unlimited km Warranty
 - No Service Plan
- Service intervals:
- 10 000km / 3 Months
 - 25 000km / 6 Months
 - 40 000km / 12 Months
- * Thereafter every 15 000km / 6 Months



BETTER DRIVE | BETTER LIFE

*Terms & Conditions apply. Offer available while stocks last. Prices may change without any prior notification. Images used are for illustrative purposes only. Actual products and specifications may vary from above information.

JAC
MOTORS



JAC N75 EV

4 TON TRUCK

SPECIFICATIONS

JACMOTORS.CO.ZA

N75 EV 4 TON TRUCK

DESCRIPTION		N75 EV 4 TON
Mass Data (kg)	GVM	7 500
	GCM	7 500
	Tare Mass	3 200
	Tare Front	1 730
	Tare Rear	1 470
	GAWR Front	3 100
	GAWR Rear	5 500
Approximate Body & Payload		4 000
Dimensional Data (mm)	Overall Length - OAL	7 025
	Wheelbase - WB	3 845
	Overall Width - OW	2 160
	Cab Width (Excluding Mirrors) - CW	1 995
	Overall Height - OH - Without Roof Fairing	2 323
	Overall Height - OH - With Roof Fairing	2 955
	Bumper To Back Of Cab - BBC	1 680
	Cab to Axle - CA	3 275
	Cab To End Of Frame - CE	5 345
	Front Overhang - FOH	1 110
	Rear Overhang - ROH	2 070
	Ground Clearance (Rear Axle)	228
	Frame Width	850
Rear Track - RT	1 650	
Powertrain System	Driving Motor Type	Permanent Magnet Synchronous Motor
	Motor Model	TZ368XSM726F
	Rated / Peak Power (kW)	65 / 130
	Rated Power Rotational Speed (rpm)	1 500 / 4 500
	Rated / Peak Torque (Nm)	415 / 1 200
	Cooling Method	Liquid
Electric Power System	Battery Type	Lithium Ion Phosphate Battery
	Single Cell Type	173Ah-1P48S
	Battery Voltage (V)	618,24
	Battery Capacity (Ah)	173
	Battery Capacity (kWh)	106,95
	Battery Weight (kg)	700
Comfort Configuration	Air Conditioning	Yes
	Heater	Yes
	Power Windows	Yes
	Central Locking	Yes
	Cruise Control	Yes
	Number Of Seats	3
	12V Accessory Power Outlet	Yes
	Radio	AM/FM Bluetooth With MP5 & USB
	Cup Holders	Yes
	Mechanical Foldable Remote Control Key	Yes

DESCRIPTION		N75 EV 4 TON
Suspension	Front & Rear	Multi-Leaf Spring With Shock Absorbers
Steering	Steering Column	Tilt And Telescoping
	Type	Recirculating Ball
	Operation	Power Assisted
Brakes	Type	Dual Circuit Air Brakes
	Anti-Lock Braking System (ABS)	Yes
	Acceleration Slip Regulation (ASR)	Yes
	Electronic Stability Control (ESC)	Yes
	Hill Start Assist (HAS)	Yes
	Advanced Emergency Brake System (AEBS)	Yes
	Electronic Park Brake (EPB)	Yes
	Air Dryer	Yes
	Front	Disc
	Rear	Drum
	Parking Brake	Spring Brake On Rear Wheels
Regenerative Braking	Yes	
Vehicle Performance	Range (C-WTVC)	≈ 200 km
	Maximum Gradeability (%)	30
	Max Geared Speed (km/h)	100
	Acceleration 0 - 50km/h	< 9 Seconds
Wheels & Tyres	Wheel Type	Single Piece Steel
	Wheel Attachment	6 Stud
	No. Of Wheels Including Spare	7
	Spare Wheel Carrier Location	Rear Of Frame
	Tyre Size	215/75R17.5 14Ply
Safety	Airbag	Driver And Passenger
	Seat Belt Warning	Driver And Passenger
	Height Adjustable Seat Belt	Driver
	Steering Wheel With Remote Controls	Cruise Control & Bluetooth Radio
	Auto Unlock Upon Collision	Yes
	LED Daytime Running Lights	Yes
	Rear Foglights	Yes
	Antilock Braking System (ABS)	Yes
	Reverse Alarm	Yes
	Rearview Camera	Yes
Power Master Switch	Yes	
Microdot Vehicle Identification	Yes	



24-Hour Roadside Assistance

STYLISH TRUCK INTERIOR



BETTER DRIVE | BETTER LIFE

*Terms & Conditions apply. Offer available while stocks last. Prices may change without any prior notification. Images used are for illustrative purposes only. Actual products and specifications may vary from above information.